

Product Name	Fax2Email Server		
Brief Description Fax2Email is a server to retrieve incoming fax. Faxes are sent out as e-mail attachments in TIFF or PDF format to selected recipients.	 <p style="text-align: center;">RS232 / LAN / DC power in (Front view)</p> <p style="text-align: right;">USB port x2 (Back view)</p>		
USB modem with fax line in & line out to fax machine USB flash (not included)	 <p style="text-align: center;">Items in packaging</p> <p style="text-align: right;">White box packaging</p>		
Model no.	FE-32		
Certification	CE, FCC, LVD, RoHS compliant		
Hardware/Firmware ver:	HFAX / F2E.xxxx		
CPU / Flash / RAM	32-Bit RISC / 4MB / 16MB		
Ports	2x USB, 1x RJ11(RS232), 1x RJ45(LAN), 1x DC Power Input		
LCD Display	LAN IP address, No. of unsent e-mails, No. of fax received, No. of fax in errors, available storage (internal / USB flash), USB Wireless connected.		
Server Size / Weight	48 x 63 x 22 mm / 75g (excluding USB modem)		
Hardware Reset	Pin hole at bottom		
Network Access	10/100 Base-T, RJ45 (Cat. 5)		
Electrical Rating	Input: 5.3V 1A Output: DC5V, 500mA (for USB port)		
Supported device	<ol style="list-style-type: none"> 1. USB Flash disk – for use to store incoming fax. Support FAT32 format. 2. <i>Compatible</i> USB Wireless – 802.11b/g dongle 3. <i>Compatible</i> USB Modem (Conexant chipset) or Serial Modem (via RJ11 port) 4. NetFeeler Mini (via RJ11 port) – for temperature, humidity, RF smoke, RF door & window sensor. 		
Supported browser	Internet Explorer, Chrome, Firefox, Safari		
Supported Fax Protocols	V.92, V.90, V.34 Data, V32bis Data, V.17 Fax, TAM, Worldwide		
Network Protocols	HTTP, TCP/IP, SMTP, Dynamic DNS, DNS Client, SNTP, DHCP.		
Operating Environment	0°C ~ 60°C at 10% ~ 90% relative humidity. <i>For indoor use only.</i>		
Packaging option	White Box / Bulk		



Package dimension	180 x 150 x 60 mm
Net(Gross) weight/set	0.25kgw(0.35kgw) <i>*subject to adaptor used</i>
Carton measurement	790 x 390 x 340 mm (50 sets per standard carton)

Mega System Technologies, Inc. reserves the right to change the specifications herein without prior notice.
Please re-confirm the specifications at time of inquiry.